



SS304/316 Lath

By AMICO Max Protection Anywhere!
ARCHITECTURAL DATA SHEET

TECHNICAL DATA

SS304 or SS316 Lath is produced to meet **ASTM C847-95**, except the metal is comprised of stainless steel alloy, not pre-galvanized carbon steel.

SS304 or SS316 Lath can be used in lieu of standard metal lath, in the same fashion as outlined in **ASTM C-1063-06**, with the following provisions:

- **Galvanized Accessories**

Accessories that come in contact with the SS Lath shall be either stainless steel or vinyl, to avoid the dissimilar metal phenomenon of galvanic corrosion.

- **Fasteners**

If standard galvanized fasteners come in contact with the SS Lath, they are to be separated by washers made of plastic, neoprene or some other inert material. Consult with fastener manufacturer as to fastener recommendations.

- **Continuous Application**

Provide separation of standard galvanized Lath and SS304/316 Lath if used in continuous application.

Specification Chart

Weight/ sq. yard	Alloy	Sheet weight	Sheet size	Sheets/ bundle
1.75 lbs.	304 or 316	approx 3.50 lbs.	27½" x 96"	10
2.5 lbs.	304 or 316	approx 5.00 lbs.	27½" x 96"	10
3.4 lbs.	304 or 316	approx 6.80 lbs.	27½" x 96"	10

Stainless Steel Lath is not in all AMICO distribution centers. Contact your representative for availability and shipping.

For any specific recommendations or application reviews, please contact:

AMICO Marketing Department • 1-800-366-2642 • Fax 205-786-6527 • clittle@gibraltar1.com



Alabama Metal Industries Corporation

United States 3245 Fayette Ave. • P.O. Box 3928 • Birmingham, AL 35208 • (205) 787-2611 • (800) 366-2642 • FAX (205) 786-6527 • sales@amico-online.com

Canada 1080 Corporate Dr. • Burlington, Ontario L7L 5R6 • (905) 335-4474 • (800) 663-4474 • FAX (905) 335-5682 • canada@amico-online.ca