


AMICO Stucco Accessories – Submittal Sheet (SHEET A)

Project: _____
 Location: _____ Contractor: _____
 Distributor: _____ Date: _____


Please indicate which of the following will be used in this project:

X-1 Corner Bead (3" Flange)




Material: Galvanized Solid Zinc Alloy
 Length: 10-ft 8-ft
 X-1N - Narrow Flange 2.5" x 2.5"

#7 FHA Weep Screed




Material: Galvanized Solid Zinc Alloy
 Length: 10-ft
 Ground: _____ inches

X-66 Casing Bead (Expanded Flange)




Material: Galvanized Solid Zinc Alloy
 Length: 10-ft
 Ground: _____ inches
 Solid Ground Punched Ground (holes)

X-2 Corner Bead (stiffer 3-1/4" flange)




Material: Galvanized Solid Zinc Alloy
 Length: 8-ft 10-ft

#15 Expansion/Control Joint




Material: Galvanized Solid Zinc Alloy
 Length: 10-ft
 Ground: _____ inches

Wire Corners (2.5" x 2.5" Flange, Zinc-coated)




Style: Straight Bullnose Arch
 Short Flange 2.5" x 1.5"
 Length: 10-ft 9-ft 8-ft

#30 Inside Corner Exp. Joint



Material: Galvanized Solid Zinc Alloy
 Length: 10-ft
 Ground: _____ inches

XJ15 Griplock J Exp./Control Joint



Material: Galvanized Solid Zinc Alloy
 Length: 10-ft
 Ground: _____ inches

#40 2-Piece Exp. Joint (thru-wall exp.)



Material: Galvanized Solid Zinc Alloy
 Length: 10-ft
 Ground: _____ inches

All AMICO accessories are produced from grade G-60 pre-galvanized steel, conforming to ASTM C-1063, or 99% pure zinc alloy.

QUALITY PRODUCTS – COAST TO COAST



A GIBRALTAR INDUSTRIES COMPANY 

ALABAMA METAL INDUSTRIES CORPORATION

3245 Fayette Ave. • Birmingham, AL 35208 • Phone (205) 787-2611 • (800) 366-2642 • Fax (205) 786-6527


www.amico-lath.com

AMICO Stucco Accessories – Submittal Sheet (SHEET B)

Project: _____
Location: _____ Contractor: _____
Distributor: _____ Date: _____


Please indicate which of the following will be used in this project:

Zinc Control Joint




Material: Solid Zinc Alloy
Length: 10-ft
Ground: _____ inches

N093 Drywall Control Joint




Material: Solid Zinc Alloy
Length: 10-ft
Ground: 3/32 inch

N-66 Narrow Wing Casing Bead




Material: Galvanized Solid Zinc Alloy
Length: 10-ft
Ground: _____ inches

Galvanized Wire (Soft Annealed Steel)




Hanger Wire - 12-ft lengths
Gauge: #8 #9 #12
 Tie Wire - 28" lengths
Gauge: #16 #18

J Metal Bead (for rigid insulation/sheathing)




Material: Galvanized
Length: 10-ft
Ground: _____ inches
 Solid Ground Punched Ground (holes)

Cold Rolled Channel



Material: Galvanized
Length: 16-ft 20-ft
Channel Size: 3/4" 1-1/2" 2"


Cornalath/Cornerite (reinforce corners)



Material: Galvanized
Size: 2" x 2" - 4-ft
 2" x 2" - 8-ft
 3" x 3" - 8-ft

All AMICO accessories are produced from grade G-60 pre-galvanized steel, conforming to ASTM C-1063, or 99% pure zinc alloy.

StripLath (reinforce doors & windows)



Material: Galvanized
Length: 8-ft
Width: 4 inches 6 inches

QUALITY PRODUCTS – COAST TO COAST



A GIBRALTAR INDUSTRIES COMPANY 

ALABAMA METAL INDUSTRIES CORPORATION

3245 Fayette Ave. • Birmingham, AL 35208 • Phone (205) 787-2611 • (800) 366-2642 • Fax (205) 786-6527

www.amico-lath.com