

AMICO *

**Stucco Beads
Drywall Beads
EIFS Beads
Vinyl Beads for
Plaster & Stucco
Applications.**

DATA

PRODUCT NAME

AMICO Rigid Vinyl (PVC) Beads Stucco Beads/
Drywall Beads/Veneer Beads/EIFS Beads

MANUFACTURER

Alabama Metal Industries Corporation (AMICO)
3245 Fayette Avenue
Birmingham, AL 35208
Phone: 205/787-2611
800/366-2642



PRODUCT DESCRIPTION

AMICO extruded vinyl beads are divided into the following groups: Stucco, Drywall/Veneer, EIFS, and Roofing. AMICO vinyl beads are manufactured from the highest quality vinyl compounds. These compounds are specially formulated for each product group individually, in order to provide products that perform optimally for specific applications. In other words, exterior products are formulated for exterior applications and interior products are formulated for interior applications.

Stucco products include corner beads, casing beads, expansion/control joints, foundation weep screeds, banding beads, reveals and soffit screeds. Drywall products include corner beads, "zipstrip" ceiling trim, and beads, bullnose corner beads, bullnose arch, soffit vents, "J" beads, "L" beads, reveals and expansions. EIFS products include

starter strips, casing, window drip edge, and corner bead. Roofing products include roof drip edge. AMICO is constantly planning and developing new products. Therefore, in an effort to keep up with industry demands, AMICO will be adding new products on a regular basis.

Composition: All exterior products (Stucco, EIFS, & Roof Drip Edge) are extruded from the highest quality exterior grade vinyl compounds, which are especially formulated for exterior applications. All interior products (Drywall) are produced from the highest quality interior grade vinyl, which is designed to be tough and durable for interior applications.

All AMICO vinyl products are long lasting and durable. They will not rust or peel and the color is solid throughout the product. AMICO vinyl products exhibit

excellent paint adhesion, with advance preparation.

AMICO beads will hold their shape, and stay true and straight when installed properly. AMICO vinyl accessories will not support or spread flame. They are self-extinguishing as soon as the heat source is removed; therefore they will not start a fire. Rigid vinyl will not conduct electricity and offers very low thermal conductivity.

TECHNICAL DATA

All material conforms to ASTM C 840, C 844, C 841, C 1047 and D 1784 for interior products, or ASTM D 4216 and C 1063 for exterior products.

INSTALLATION

Methods of Cutting: Vinyl beads can be cut with hand snips or for larger products with a fine toothed saw, such as a hacksaw.

Methods of Attachment: Vinyl drywall beads are usually stapled in place using 9/16" type G staples, but drywall nails or screws may be used. Do not sink these too deep as they may deform the nailing flange. Beads should be attached at the top on one side, then on the bottom of the same side after bead is straightened. Attach one side in its entirety before attaching the other side. If the bead is attached horizontally, the top flange should be completely attached before attaching the bottom flange. ALL BUTT JOINTS, INTERSECTIONS, AND ENDS SHOULD BE CAULKED.

Vinyl stucco beads may be attached by the use of lathing nails, lath screws, or wire ties. Where temperatures may vary greatly during construction, plaster beads should be nailed directly to studs, rather than wire tied to lath. Never clean out expansion joints with sharp implements, such as trowels. Such implements may score or tear the joint resulting in a leak. Removable tape is provided to keep expansion joints clean during the finishing process and should be removed after the finish is in place. All AMICO vinyl stucco beads are provided with adequate perforations to allow for complete embedment and key-

ing of stucco or finishing compound. Perforations, as well as surface ridges are provided in drywall and veneer beads to allow the finishing compound to penetrate the bead and allow for complete bonding of the joint compound or veneer plaster.

AVAILABILITY AND COST

AMICO vinyl beads are sold nationally through a network of dealers and distributors. To locate the dealer nearest you, call 1-800/366-2642. Current cost may be obtained by contacting your nearest dealer.

WARRANTY

These AMICO products are warranted to the finished product specification and to the physical and chemical properties of the raw material used if requested prior to the sale and expressly stated by AMICO and AMICO's supplier.

This warranty is limited to one year from the date the product is used for its intended purpose.

The information herein is accurate and reliable to the best of our knowledge. AMICO has no control over installation, workmanship, accessories, complementary materials, or conditions of ap-

plication and therefore, cannot be responsible for these areas of product performance.

THE EXCLUSIVE REMEDY FOR ANY BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR A REFUND OF THE PURCHASE PRICE AT AMICO'S OPTION. THE ABOVE STATED WARRANTIES AND REMEDY IS THE ONLY WARRANTY MADE AND AMICO DISCLAIMS ANY OTHER WARRANTY WHETHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

MAINTENANCE

Vinyl beads should be given reasonable protection from the elements prior to installation. Caution should be taken to avoid damage to the product and also care should be given not to store anything on top of these products that might deform their shape prior to usage.

TECHNICAL SERVICES

Technical service is available form



ALABAMA METAL INDUSTRIES CORPORATION
3245 Fayette Ave - Birmingham, AL 35208
800-366-2642 - FAX 205-780-7838